

PRODUCT DATA SHEET

DI-LUBE 150

Di-Lube 150 is water base dilutable die release agent for Aluminum pressure die-casting. It provides excellent release for complex molds with bright surface finish.

DI-Lube 150 is a balance formula of synthetic Lubricant and additive package. Better parting and bright surface can be achieved in complex molds. The additive package also lubricates ejector pins and moving parts effectively to reduce wear and tear.

Di-Lube 150 can be used in automatic and hand spray guns effectively. The dilution ratio can be minimum 50 and for simple mold up to 200.

Di-Lube 150 does not contain metallic compounds or silicones.

Specification: -


- Colour : Milky white.
- Base oil : Synthetic.
- Density : 0.97 ± 0.03
- Flash Point : None (Contains water)
- Shelf Life : 6 to 9 months in original container.

Application: - Dilute Di-Lube 150 in water in the required ratio. It mixes easily with water with little agitation. The dilution ratio can be 50 for complex mould to 200. The ratio however depends and finalized by evaluation. Di-Lube 150 is to be stored below 50⁰C in covered area in close condition.

Packing: - 20/ 50 Liter carboy.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

 LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com