

PRODUCT DATA SHEET

PLUNGERGUARD PRO-200
(Plunger Lubricants)

Lubrall Plunger Guard Pro 200 is a specialized lubricant designed for use in pressure die-casting machines. Its primary function is to minimize wear on the plunger tip and sleeve, which are critical components in the die-casting process. By reducing wear, Plunger Guard Pro 200 helps to increase the lifetime of these components, leading to longer intervals between maintenance and replacement. The formulation of Plunger Guard Pro 200 is tailored to withstand the high pressures and temperatures encountered in die-casting operations. It provides a protective film that reduces friction between the plunger and the sleeve, ensuring smooth operation and preventing damage due to metal-to-metal contact. Overall, the use of Lubrall's Plunger Guard Pro 200 can result in improved machine efficiency, reduced downtime for maintenance, and ultimately, cost savings for die-casting operations.

APPLICATION :

- Plunger Lubrication for Pressure Diecasting machine

Specification

1	Colour	Yellow Liquid
2	Density @29	0.850-0.880
3	Viscosity @ 40	180-200 Cst
4	Flash Point	>200⁰ C
5	Corrosion Test	Pass
6	Pour Point	< - 3⁰ C
7	Viscosity Index	125

Packing: - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."



LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com