

**PRODUCT DATA SHEET
LUBRALL SEAL-AMS**

Lubrall SEAL-AMS is a quick-drying rust preventive oil that forms a hard protective film on metal surfaces, ideal for temporary protection of ferrous and non-ferrous parts. It's specifically designed for safeguarding non-moving parts and components from rust and corrosion and rust protection duration is 9-12 months.

Key Features and Benefits:

- **Quick Drying:** Dries rapidly for efficient application.
- **Hard Film:** Durable layer resists wear and environmental factors.
- **Versatile Protection:** Suitable for both ferrous and non-ferrous metals.
- **Non-Moving Parts:** Protects inactive components.

Application Areas:

- **Manufacturing and Industrial:** Protects machinery parts and tools in storage.
- **Automotive:** Safeguards temporarily stored parts.
- **Aerospace:** Maintains rust-free components in long-term storage.
- **Construction:** Shields materials and equipment parts.
- **Marine:** Provides rust protection in marine environments.

Usage Instructions:

1. **Clean Surface:** Remove dirt, grease, or rust.
2. **Apply Evenly:** Use a brush, spray, or dip method.
3. **Dry:** Allow to dry completely, forming a layer.
4. **Remove Film:** Use a solvent if necessary.


Specification

1	Colour	Golden Yellow
2	Odour	Orange Mild
3	Specific Gravity	0.850-0.885
4	Flash Point	>40°C
5	Film Thickness	1 to 3 Micron
6	Drying Time	10 Min
7	Salt Spray Test	Pass:
8	Water Displacement Test IS 1154	Not Applicable

Packing: - 35 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."


LUBRALL INDUSTRIES PVT LTD
 PLOT NO: B-73/1/2/3, CHAKAN MIDC,
 PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com