

PRODUCT DATA SHEET  
**LUBRALL SEAL-DW**  
(Rust preventive oil)

**Lubrall SEAL - DW** is a solvent-based dewatering type rust preventive oil designed to protect metal surfaces from rust and corrosion. It is formulated to displace moisture from metal surfaces, providing a protective barrier against the elements. This rust preventive oil is especially effective in preventing rust during storage or shipment of metal parts and equipment. SEAL - DW is easy to apply and can be sprayed or brushed onto metal surfaces. It forms a thin, transparent film that adheres well to the metal, providing long-lasting protection against rust and corrosion.

**APPLICATION:**

Lubrall's SEAL-DW short-term rust prevention oil is specifically designed for indoor use, providing effective rust prevention for a period of 3-4 months. It is ideal for protecting metal surfaces during storage or transit in indoor environments where exposure to moisture and humidity is a concern. SEAL-DW forms a thin, protective film that adheres to metal surfaces, preventing the formation of rust and corrosion. It is easy to apply and can be sprayed or brushed onto metal surfaces, providing reliable rust protection for short-term storage needs.

**Advantages:**

**Effective Rust Prevention:** SEAL-DW effectively prevents rust and corrosion on metal surfaces by displacing moisture and forming a protective barrier.

**Indoor Use:** SEAL-DW is designed for indoor use, making it ideal for protecting metal parts and equipment stored in indoor environments.

**Short-Term Protection:** SEAL-DW provides short-term rust protection for 3-4 months, making it suitable for short-term storage needs.

**Easy Application:** SEAL-DW is easy to apply and can be sprayed or brushed onto metal surfaces, ensuring thorough coverage. **Transparent Film:** SEAL-DW forms a thin, transparent film that adheres well to metal surfaces without leaving a greasy residue.

**Specification:**

<b>1</b>	<b>Colour</b>	<b>Yellow</b>
<b>2</b>	<b>Density @29</b>	<b>0.823-0.860</b>
<b>3</b>	<b>Viscosity</b>	<b>2.2 Cst</b>
<b>4</b>	<b>Water Displacement Test</b>	<b>Pass</b>
<b>5</b>	<b>Salt Spray Test</b>	<b>48 Hours Pass</b>
<b>6</b>	<b>Flash Point</b>	<b>&gt; 65<sup>0</sup> C</b>

**Packing:** - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

**"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."**



LUBRALL INDUSTRIES PVT LTD  
PLOT NO: B-73/1/2/3, CHAKAN MIDC,  
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507  
[www.lubrall.com](http://www.lubrall.com) email- lubralloil@gmail.com