

PRODUCT DATA SHEET

**SEAL-DW-39**

Lubrall SEAL-DW-39 is a solvent-base with wax, non-water-soluble rust preventive oil designed for robust metal protection. This clear brown fluid is ideal for both domestic and export applications, ensuring metal components remain rust-free during storage and transit. And rust protection duration of SEAL-39 is 6-8 months.

**Key Features and Benefits:**

- **Solvent-Based:** Ensures thorough and even coverage.
- **Non-Water Soluble:** Superior protection in wet environments.
- **Clear Brown Fluid:** Easy to apply and inspect.
- **Versatile:** Suitable for various industries.

**Application Areas:**

- **Manufacturing and Industrial:** Protects machinery, tools, and parts.
- **Automotive:** Safeguards components during storage and transit.
- **Aerospace:** Maintains parts and assemblies rust-free.
- **Construction:** Shields materials and equipment.
- **Marine:** Effective in marine environments.

**Usage Instructions:**

1. **Clean Surface:** Ensure metal is free from contaminants.
2. **Apply Evenly:** Use a brush, spray, or dip method.
3. **Dry:** Allow solvent to evaporate.
4. **Remove Film:** Use solvent if necessary.


**Specification:**

1	<b>Colour</b>	Yellowish
2	<b>Odour</b>	Mild Organic
3	<b>Specific Gravity</b>	0.825-0.850
4	<b>Flash Point</b>	> 65°C
5	<b>Film Thickness</b>	>1 Micron
6	<b>Drying Time</b>	30 Min
7	<b>Salt Spray Test</b>	72 Hour Pass
8	<b>Water Displacement Test IS 1154</b>	Pass

**Packing:** - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

**"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."**

 LUBRALL INDUSTRIES PVT LTD  
PLOT NO: B-73/1/2/3, CHAKAN MIDC,  
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507  
[www.lubrall.com](http://www.lubrall.com) email- lubralloil@gmail.com