

#### PRODUCT DATA SHEET

## SEAL-DW-40

(Rust preventive oil)

Lubrall SEAL DW 40 is a highly effective rust preventive oil designed for short-term rust protection, suitable for domestic use. This oil excels in water displacement, ensuring that moisture is quickly and efficiently removed from metal surfaces, thereby preventing corrosion.& rust protection duration is 2-3 Month.

### **Key Features of SEAL DW 40:**

- **Short-Term Protection:** SEAL DW 40 offers reliable rust protection for up to one month in outdoor conditions. It is ideal for applications where temporary rust prevention is required. **Water Displacing Properties:** One of the standout features of SEAL DW 40 is its excellent water displacing capability. This ensures that water is swiftly removed from the surface, which is crucial for preventing rust in humid or wet conditions.
- **Domestic Use:** SEAL DW 40 is formulated for domestic applications, making it suitable for protecting tools, garden equipment, and other metal items around the house.
- **Thin Film Formation**: This oil forms a thin, 1-micron protective film on the metal surface. The thin film ensures comprehensive coverage without affecting the functionality or appearance of the metal parts.

# **Application Areas:**

- **Tools and Equipment:** Ideal for coating tools, machinery parts, and other metal objects to prevent rust during storage.
- **Garden and Outdoor Equipment:** Protects Garden tools, outdoor furniture, and other equipment from the elements.
- **Household Metal Items:** Useful for preserving metal objects used in domestic environments, ensuring they remain rust-free even in damp conditions.
- Overall, Lubrall SEAL DW 40 is a versatile and effective rust preventive oil designed to meet the needs of domestic users, providing short-term protection and excellent water displacement in a convenient and user-friendly formulation.

### **Specification:**

1	Colour	Light Yellow
2	Density @29	0.810-0.830
3	Viscosity	> 2
4	Water Displacement Test	Pass
5	Salt Spray Test	24 Hours Pass
6	Flash Point	> 65 ° C

**Packing:** - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

### "FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

