

**PRODUCT DATA SHEET  
LUBRALL SEAL DW-60**

**Lubrall SEAL DW-60** is a high-performance rust preventive oil specifically formulated to offer superior rust protection for various applications. Renowned for its excellent rust prevention capabilities, SEAL DW-60 provides reliable protection for up to 6-8 months, making it an ideal choice for both domestic and export applications.

**Key Features:**

**Exceptional Rust Protection:** Creates a robust barrier against corrosion, effective in high humidity and corrosive environments.

**Water Resistance:** Excellent water resistance enhances protection against rust and corrosion.

**Long-Term Protection:** Suitable for both short-term and long-term storage.

**Film Type:** Forms a thin, 1.5-micron protective film.

**Flash Point:** Safe to handle with a flash point greater than 50°C.

**Lubrall SEAL DW-60** is the dependable choice for long-term rust protection in a variety of industrial applications.

**Specification**

<b>1</b>	<b>Colour</b>	Pale Brown Fluid
<b>2</b>	<b>Odour</b>	Mild
<b>3</b>	<b>Specific Gravity</b>	0.810-0.830
<b>4</b>	<b>Flash Point</b>	>65
<b>5</b>	<b>Film Thickness</b>	< 1
<b>6</b>	<b>Drying Time</b>	30 Min
<b>7</b>	<b>Salt Spray Test</b>	48 Hour Pass
<b>8</b>	<b>Water Displacement Test IS 1154</b>	Pass

**Packing:** - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

**"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."**

 LUBRALL INDUSTRIES PVT LTD

PLOT NO: B-73/1/2/3, CHAKAN MIDC,

PHASE NO -II, BHAMBOLI, DIST- PUNE-410507

[www.lubrall.com](http://www.lubrall.com) email- lubralloil@gmail.com