

PRODUCT DATA SHEET
LUBRALL SEAL DW-80

Lubrall SEAL DW-80 is a specialized rust preventive oil designed for both ferrous and nonferrous metals, offering up to 12 months of rust protection. This makes it ideal for domestic and export applications, where metals are exposed to corrosive environments during prolonged storage or transportation.

Key Features and Benefits

- **Comprehensive Protection:** Keeps metals corrosion-free for long periods.
- **Versatile:** Works on both ferrous and nonferrous metals.
- **Durable Barrier:** 1.5-to-2-micron film shields against moisture and oxygen.
- **For Domestic and Export Use:** Handles varying climates and long transits.
- **Easy Application and Removal:** Simple to apply and remove, preserving metal condition.

Application Areas

- **Manufacturing and Industrial:** Protects machinery, tools, and parts during extended storage.
- **Automotive:** Safeguards automotive components in storage and shipping.
- **Aerospace:** Protects parts and assemblies during long-term storage.

Usage Instructions

1. **Surface Preparation:** Clean the metal surface.
2. **Application:** Apply evenly using a brush, spray, or dip method.
3. **Drying:** Allow the film to dry and set.
4. **Removal:** Use an appropriate solvent or cleaner to remove the film.

Specification

1	Colour	Pale Yellow
2	Odour	Mild Organic
3	Specific Gravity	0.825-0.830
4	Flash Point	> 65°C
5	Film Thickness	< 2 Micron
6	Drying Time	30 Min.
7	Salt Spray Test	100 Hour Pass
8	Water Displacement Test IS 1154	Pass

Packing: - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

🔴 LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com