

## PRODUCT DATA SHEET LUBRALL SEAL-EXP-9060

**LUBRALL SEAL-EXP-9060** is a solvent-based, non-water-soluble rust preventive oil designed for long-lasting metal protection. This clear brown fluid is ideal for both indoor and outdoor packed storage in various industrial and commercial applications.

# **Key Features and Benefits**

- Solvent-Based: Ensures thorough and even coverage.
- Non-Water Soluble: Superior protection against water exposure.
- Clear Brown Fluid: Easy to apply and inspect.
- High Flash Point: Safe to use with a flash point over 75°C.
- Long-Term Protection: Up to 5 years indoors and 1 year outdoors when packed.

## **Application Areas**

- Manufacturing and Industrial: Protects machinery, tools, and parts.
- Automotive: Safeguards components during storage and transit.
- Aerospace: Maintains parts rust-free during extended storage.
- Construction: Shields materials and equipment.
- Marine: Effective in marine environments.

### **Usage Instructions**

- 1. Clean Surface: Ensure the metal is free from contaminants.
- 2. Apply Evenly: Use a brush, spray, or dip method.
- 3. Dry: Let the solvent evaporate to form a protective barrier.
- 4. **Remove Film**: Use an appropriate solvent if necessary.

S	pecification	
D	Jeemication	

1	Colour	Brownish	
2	Odour	Mild Organic	
3	Specific Gravity	0.800-0.840	
4	Flash Point	>75° <b>C</b>	
5	Film Thickness	2-3 Micron	
6	Drying Time	>30 Min	
7	Salt Spray Test	180 Hours Pass	
8	Water Displacement Test IS 1154	Pass	

Packing: - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

### "FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

LUBRALL INDUSTRIES PVT LTD PLOT NO: B-73/1/2/3, CHAKAN MIDC, PHASE NO -II, BHAMBOLI, DIST- PUNE-410507 www.lubrall.com email- lubralloil@gmail.com