

# PRODUCT DATA SHEET LUBRALL SEAL-QC-500

**Lubrall SEAL-QC-500** is an oil-based rust preventive that forms a non-drying, oily film on metal surfaces, providing 3 to 5 months of protection. Ideal for rust prevention in various industrial and commercial applications, it ensures reliable rust protection.

### **Key Features and Benefits:**

- **Non-Drying**: Forms a lasting, oily film.
- **High Viscosity**: Ensures thorough coverage and adhesion.
- Oil-Based: Robust rust and corrosion protection.

# **Application Areas:**

- Manufacturing and Industrial: Protects machinery parts and components.
- Automotive: Safeguards stored or awaiting parts.
- Aerospace: Keeps components rust-free during short-term storage.
- Marine: Temporary protection for metal parts.

# **Usage Instructions:**

- 1. Clean Surface: Remove contaminants like dirt and grease.
- 2. **Apply Evenly**: Use a brush, spray, or dipping method.
- 3. **Remove Film**: Use an appropriate solvent or cleaner before use.

# **Specification:**

1	Colour	Brownish
2	Odour	Odourless
3	Specific Gravity	0.850 -0.870
4	Flash Point	> 180° <b>C</b>
5	Film Thickness	> 1 Micron
6	Drying Time	Non-Drying
7	Salt Spray Test	72 Hours
8	Water Displacement Test IS 1154	Not Applicable

**Packing:** - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

#### "FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO.

♦ LUBRALL INDUSTRIES PVT LTD PLOT NO: B-73/1/2/3, CHAKAN MIDC, PHASE NO -II, BHAMBOLI, DIST- PUNE-410507 www.lubrall.com email- lubralloil@gmail.com